2025 MAVERICK X3 X MR TURBO RR 72"



Hyper Silver & Legion Red

| ENGINE | TURBO RR |
|----------------------|--|
| Туре | 200 hp, Rotax [®] ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler, high-performance air filter and strategically positioned engine air intake |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) |
| Transmission | pDrive primary and Quick Response System X (QRS-X) CVT, high airflow with strategically positioned CVT air intake and exhaust, L / H / N / R / P |
| Drive Train | Lockable front differential with exclusive Smart-Lok* technology True 4-modes traction system: 2WD / 4WD with front diff. lock / 4WD MUD / 4WD TRAIL |
| Power Steering | High-torque Tri-Mode Dynamic Power Steering (DPS™) |
| SUSPENSIONS | |
| Front Suspension | Double arched A-arm with sway bar / 22 in. (55.9 cm) suspension travel Trophy Truck-inspired arms |
| Front Shocks | FOX ¹ 2.5 PODIUM Piggyback with QS3 [†] compression adjustment |
| Rear Suspension | 4-link Torsional Trailing Arm X (TTX) with sway bar and arched lower links / 22 in. (55.9 cm) suspension travel |
| Rear Shocks | FOX [†] 2.5 PODIUM Piggyback with QS3 [†] compression adjustment and bottom-out control |
| TIRES & WHEELS | |
| Front / Rear Tires | ITP Cryptid 30 x 9/11 x 14 in. |
| Wheels | 14 in. cast-aluminum beadlock |
| BRAKES | |
| Front | Dual 262 mm disc brakes with hydraulic twin-piston calipers |
| Rear | Dual 248 mm disc brakes with hydraulic twin-piston calipers |

PACKAGE HIGHLIGHTS

- Smart-Lok[™]* front differential
- FOX[†] 2.5 PODIUM QS3 Piggyback shocks
- Snorkeled engine air intake and CVT
- Belt-monitoring system
- 850 W magneto
- 30 in. ITP Cryptid tires
- 14 in. aluminum beadlock wheels
- Front bumper, half-doors
- 4,500 lb (2,041 kg) winch with synthetic rope
- HMWPE full skid plate
- · Front and rear tow hooks
- 7.6 in. digital display with keypad
- · X-package graphics / seats
- Can-Am LED signature

| Estimated Dry Weight | 1,758 lb (797.4 kg) |
|----------------------|---|
| Chassis / Cage | Dual-phase 980 steel |
| LxWxH | 132.3 x 74.2 x 68 in. (336 x 188.5 x 172.7 cm) |
| Wheelbase | 102 in. (259.1 cm) |
| Ground Clearance | 16 in. (40.6 cm) |
| Rack Capacity | 200 lb (91 kg) with LinQ™ quick-attach |
| Storage Capacity | Total: 2.5 gal (9.4 L) |
| Fuel Capacity | 10.5 gal (40 L) |
| FEATURES | |
| Gauge | 7.6 in. wide digital display with keypad |
| Instrumentation | DC outlet (10 A) |
| Anti-Theft System | RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button |
| Lighting | LED headlights LED signature LED tail lights |
| Winch | 4,500 lb (2,041 kg) winch with synthetic rope |
| Magneto | 850 W |
| Protection | Front bumper Half-doors Front and rear tow hooks HMWPE full skid plate |
| WARRANTY & EXTEN | DED SERVICE |
| Factory Warranty | 6-month BRP limited warranty |
| Extended Service | B.E.S.T. term available up to 30 months |



© 2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. @, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. † Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, pice, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SXS) operator's guide and watch the safety DD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SxSs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 12 years old an able to hol hand grips and plant feet while seated against the backrest. Never engage in stund triving and avoid excessive speed. Ride responsibly. "Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry. Top Speed is limited to a maximum of 100 km/h (62 mph).

